National Institute of Technology Rourkela

Departmental Seminar	
Seminar Title	: Return seminar -UTILIZING LIGNOCELLULOSIC WASTE FOR EXTRACTION AND CHARACTERIZATION OF CELLULOSE AND NANOCELLULOSE
Speaker	: Subhanki Padhi
Supervisor	: 2910
Venue	: CH 306
Date and Time	: 26 Sep 2024 (5.15 pm)
Abstract	: Background: The lignocellulosic wastes can be utilized for extraction of cellulose and nanocellulose which not only reduces environmental stress but also adds to economic growth. Nanocellulose possesses excellent barrier properties, mechanical strength, crystallinity, and thermal stability, making it a perfect material for a wide range of applications. Being an efficient and rapid process, acid hydrolysis was used for the extraction of nanocellulose. Methods: In this work, jackfruit peel was used for the extraction of cellulose and further its conversion to nanocellulose using acid hydrolysis process. Jackfruit peel was treated with alkali and bleaching agents to remove the non-cellulosic materials and isolate pure cellulose. Further, different inorganic acids (sulphuric acid, hydrochloric acid, and phosphoric acid) and organic acids (formic acid, citric acid, oxalic acid) of 6M concentration were used for acid hydrolysis to obtain nanocellulose at 80°C for 3 h. The impact of different organic and inorganic acids was evaluated based on particle size, zeta potential, crystallinity, microstructure, and thermal stability. Results: The yield of cellulose with average particle size of 100 - 160 nm, whereas it was 170 - 250 nm for organic acid hydrolysed nanocellulose. The FTIR spectra of cellulose and nanocellulose powder confirmed the removal of lignin and hemicellulose and confirmed that the absorption bands of cellulose remained intact in the case of nanocellulose. The crystallinity of nanocellulose. Conclusions: This study emphasized the importance of acid strength in controlling the dissociation of hydrogen bonds and affecting the properties of nanocellulose, Acid hydrolysis