Registration Seminar	
Seminar Title	: Incorporating Jute Biochar in Cement Mortar for Improved Mechanical Properties and Carbon Footprint Reduction
Speaker	: Binson Chalissery Johnson (Rollno : 523ce1004)
Supervisor	: Mahendra Gattu
Venue	: CE Seminar Hall
Date and Time	: 09 May 2025 (10 am)
Abstract	The environmental burden of cement production, especially its high carbon emissions, has led to the exploration of sustainable cement replacements. This study focuses on the utilization of jute-derived biochar (JBC) as a partial ceme substitute in mortar to improve mechanical performance and reduce carbon footprint. Jute fibers were pyrolyzed at 400°C to produce fine biochar, which was then incorporated into cement mortar at varying dosages (0%, 1%, 3%, and 5% by weight of cement). The biochar was characterized by CHNS elemental analysis (carbon content ~69.3%) and FESEM imaging, revealing a porous morphology that supports enhanced matrix bonding.
	Two sets of mortar specimens (Series A and B) were tested to validate performance. In Series A, the 3% biochar mi (JBC-A3) achieved the highest compressive strength of 32.28 MPa at 28 days, an increase of ~19.4% compared to the control (27.02 MPa). Similarly, in Series B, the 3% mix (JBC-B2) attained 23.96 MPa at 28 days, slightly higher than the control mix (22.8 MPa). Both data sets show that the optimum compressive strength was consistently observed at 3% biochar replacement, while higher dosages (5%) and lower dosages (1%) resulted in reduced performance. For example, in Series B, the 1% mix dropped to 19.27 MPa, indicating poor early hydration and reduced cement content.
	Early-age strength (7 and 14 days) also followed this trend, with JBC-B2 (3%) outperforming the control at all curing ages. Overall, the inclusion of 3% jute biochar offers a balanced improvement in compressive strength, material sustainability, and carbon reduction, making it a viable additive in eco-efficient mortar production.

Keywords: Jute biochar, cement mortar, compressive strength, pyrolysis, sustainable construction, CHNS analysis, FESEM, low-carbon building materials